


TOUCH 156L



COLOUR





15.6" Panel PC capacitive and with touch screen. It has been designed to be used in a wide range of applications for supervision and technology control.

The Panel can act in two modes:

1) HMI for displaying websites running on a third-party controller 2) If WEBserver application is enabled, the Panel can itself communicate with other devices through available protocols (BACnet, Modbus, HelvarNet, SNMP, MQTT, UDP etc.). Visualization is created directly in the Panel via a web editor.

KEY FEATURES



Suitable for extreme conditions

(resistant to water and dust, shocks and EMC emissions)

Safe and stable operation thanks to the Linux OS Without rotating parts



Accessories for wall mount as well as for a mounting to a panel

Powerful software for integration and supervisory

TYPICAL USAGE



Supervision and control of a production technologies Supervision and control of building technologies

(heating, cooling, air-conditiong, lighting, shading etc.)

Digital signaler and information kiosks Reservation and attendance systems

SPECIFICATION

Display	
Size	15.6" / 16:9
Resolution	1920 x 1080 px
Contrast	1000:1
Luminance standard	300 nit
Display colors	16,7M (8-bit)
Technology	IPS, capacitive touch screen

Performance	
CPU	Intel Celeron 2.0 GHz
Operating memory	4 GB [⋆]
Flash drive	64 GB SSD*
OS	Linux*

Interfaces	
Power Consumption	24 VDC / max 75 W
Ethernet	1 x RJ 45 (10/100 base-T)
Wi-Fi	802.11a/b/g/n
COM	2 x RS-232
External interfaces	USB, VGA, HDMI

Housing and Environment		
Dimensions	228 x 53 x 330 mm/2,3 kg	
Construction	aluminum, black	
Protection	IP65	
Operating conditons	-10°C to 70°C/10% to 80%	
Certification	CE, FCC, RoHS, ISO	